

1.3 Rotary Pads Laminated

Laminated Backing pad for general-purpose sanding/polishing

With nylon support backing plate, laminated with soft EVA foam
Close-cell Foam, ideal for both dry & wet polishing



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Foam Thickness
14120-11	2" (50mm)	5/8"-11		✓	12000	Medium	10mm
14120-21	2" (50mm)	M14-2		✓	12000	Medium	10mm
14120-31	2" (50mm)	M10-1.5		✓	12000	Medium	10mm
14120-12	2" (50mm)	5/8"-11	✓		12000	Medium	10mm
14120-22	2" (50mm)	M14-2	✓		12000	Medium	10mm
14120-32	2" (50mm)	M10-1.5	✓		12000	Medium	10mm
14130-11	3" (74mm)	5/8"-11		✓	12000	Medium	10mm
14130-21	3" (74mm)	M14-2		✓	12000	Medium	10mm
14130-12	3" (74mm)	5/8"-11	✓		12000	Medium	10mm
14130-22	3" (74mm)	M14-2	✓		12000	Medium	10mm

* Remark: Optional straight or bevel cut edge and water feed hole



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Remark	Foam Thickness
11040-1	4" (100mm)	M10-1.5	✓		12000	Medium	10mm
11045-2	4.5" (115mm)	M14-2	✓		12000	Medium	10mm
11050-2	5" (125mm)	M14-2	✓		12000	Medium	10mm
11060-2	6" (150mm)	M14-2	✓		10000	Medium	10mm

* Remark: Optional straight or bevel cut edge and water feed hole



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Foam Thickness
14165-1	6.5" (165mm)	5/8"-11	✓		6000	Medium	10mm
14165-2	6.5" (165mm)	M14-2	✓		6000	Medium	10mm
14165-3	6.5" (165mm)	M16-2	✓		6000	Medium	10mm