

## 10.1 Rotary Pads FlexEdge

# FlexEdge™

Molded PU Backing Pads for foam pads and wool pads



The FlexEdge™ Urethane Backing Pads are the indispensable part of achieving the perfect polishing finish.

The edge of pad is wide and soft, when making the carved surface polishing, the pad edge can bend on the curvature of the polishing surface, and provide the excellent operating finish.

The moulding technics makes the permanent bond for the components of the pad and eliminates ungluing problems. The microcellular Urethane foam has the good rebound performance and can absorb the vibration. It does not deform permanently, and is extremely tough and durable to withstand the rigorous operation

The Velcro(R) hook facing is adopted, it is molded with the Urethane foam and creates a permanent durable and flat surface.



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density
14231-22	3" (74mm)	M14-2	✓		12000	Soft
14231-32	3" (74mm)	M10-1.5	✓		12000	Soft



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density
13051-12	5" (123mm)	5/8"-11	✓		10000	Medium
13051-22	5" (123mm)	M14-2	✓		10000	Medium
13051-32	5" (123mm)	M16-2	✓		10000	Medium



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density
13060-1	6" (150mm)	5/8"-11	✓		7000	Medium
13060-2	6" (150mm)	M14-2	✓		7000	Medium
13060-3	6" (150mm)	M16-2	✓		7000	Medium
13063-1	6.3" (160mm)	5/8"-11	✓		7000	Medium
13063-2	6.3" (160mm)	M14-2	✓		7000	Medium
13063-3	6.3" (160mm)	M16-2	✓		7000	Medium



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density
12170-11	7" (180mm)	5/8"-11		✓	6000	Medium
12170-12	7" (180mm)	5/8"-11	✓		6000	Medium
12170-21	7" (180mm)	M14-2		✓	6000	Medium
12170-22	7" (180mm)	M14-2	✓		6000	Medium

Remark: Optional centering hole and canvas face upon request



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density
12270-12	7" (180mm)	5/8"-11	✓		6000	Soft
12270-22	7" (180mm)	M14-2	✓		6000	Soft
12263-12	6.3" (160mm)	5/8"-11	✓		6000	Medium

Remark: Optional centering hole and canvas face upon request