

10.2 Rotary Pads FlexEdge

FlexEdge™

Backing pads for recessed foam pads and wool buffing pads
 Ideal for work with recessed 8"-9" foam pads, and 8" single side wool pads



Item No.	Size	Thread	Velcro	Max.RPM	Density	Remark
13068-1	6.8" (175mm)	5/8"-11	✓	6000	Medium	
13068-2	6.8" (175mm)	M14-2	✓	6000	Medium	
13068-3	6.8" (175mm)	M16-2	✓	6000	Medium	
13065-1	6.5" (167mm)	5/8"-11	✓	6000	Medium	
13065-2	6.5" (167mm)	M14-2	✓	6000	Medium	
13065-3	6.5" (167mm)	M16-2	✓	6000	Medium	



Item No.	Size	Thread	Velcro	Max.RPM	Density	Remark
14268-1	6.8" (175mm)	5/8"-11	✓	6000	Medium	
14268-2	6.8" (175mm)	M14-2	✓	6000	Medium	
14268-3	6.8" (175mm)	M16-2	✓	6000	Medium	



Item No.	Size	Thread	Velcro	Max.RPM	Density	Foam Thickness
14165-1	6.5" (165mm)	5/8"-11	✓	6000	Medium	10mm
14165-2	6.5" (165mm)	M14-2	✓	6000	Medium	10mm
14165-3	6.5" (165mm)	M16-2	✓	6000	Medium	10mm

W68 Backing Pads for Rotary Polisher

Work with 7" foam pads



Item No.	Size	Thread	Velcro	Max.RPM	Density	Remark
10161-122	6" (152mm)	5/8"-11	✓	6000	Medium	
10161-222	6" (152mm)	M14-2	✓	6000	Medium	
10161-322	6" (152mm)	M16-2	✓	6000	Medium	



W68DA Backing Pads for Oribal Polisher

Work with 7" foam pads



Item No.	Size	Thread	Velcro	Max.OPM	Density	Weight	Remark
24061-122	6" (152mm)	5/16"-24	✓	8000	Medium	110g	For DA Polisher

