

3.3 Classic DA Pads

Dual Action Sander Backing Pads, low profile

PUR molded, Medium density , good rebounding and durability.
Pad with fixed 5/16"-24 bolt



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Hole	Weight	Thickness
21040-2	4" (98mm)	5/16"-24	✓		12000	Medium	no hole	100g	14.5mm
21050-1	5" (123mm)	5/16"-24		✓	12000	Medium	no hole	100g	9.5mm
21050-2	5" (123mm)	5/16"-24	✓		12000	Medium	no hole	100g	9.5mm
21150-1	5" (123mm)	5/16"-24		✓	12000	Medium	3+3	100g	9.5mm
21150-2	5" (123mm)	5/16"-24	✓		12000	Medium	3+3	100g	9.5mm
21250-1	5" (123mm)	5/16"-24		✓	12000	Medium	5	100g	9.5mm
21250-2	5" (123mm)	5/16"-24	✓		12000	Medium	5	100g	9.5mm
21350-1	5" (123mm)	5/16"-24		✓	12000	Medium	8	100g	9.5mm
21350-2	5" (123mm)	5/16"-24	✓		12000	Medium	8	100g	9.5mm



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Hole	Weight	Thickness
21060-1	6" (148mm)	5/16"-24		✓	12000	Medium	no hole	125g	9.5mm
21060-2	6" (148mm)	5/16"-24	✓		12000	Medium	no hole	125g	9.5mm
21160-1	6" (148mm)	5/16"-24		✓	12000	Medium	6	125g	9.5mm
21160-2	6" (148mm)	5/16"-24	✓		12000	Medium	6	125g	9.5mm

Dual Action Sander Backing Pads, Middle Profile, Bevel Edge

PUR molded, Medium density , good rebounding and durability.
Pad with fixed 5/16"-24 bolt



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Hole	Weight	Thickness
22050-1	5" (123mm)	5/16"-24		✓	12000	Medium	no hole	100g	14.5mm
22050-2	5" (123mm)	5/16"-24	✓		12000	Medium	no hole	100g	14.5mm
22250-1	5" (123mm)	5/16"-24		✓	12000	Medium	5	100g	14.5mm
22250-2	5" (123mm)	5/16"-24	✓		12000	Medium	5	100g	14.5mm
22060-1	6" (148mm)	5/16"-24		✓	12000	Medium	no hole	125g	14.5mm
22060-2	6" (148mm)	5/16"-24	✓		12000	Medium	no hole	125g	14.5mm