

3.4 Pro-Quality DA Backing Pads



The backing pad is the key component for building a non-vibration air sander. SunnyPads works with many world-class pneumatic manufacturers closely, developed a specially designed series of pads for tool factory supply. For its outstanding performance, we call this series of pad as Pro-Quality .

Straight Edge DA Backing Pads



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Hole	Weight	Thickness
23050-1	5" (123mm)	5/16"-24		✓	12000	Medium	no hole	100g	8.7mm
23050-2	5" (123mm)	5/16"-24	✓		12000	Medium	no hole	100g	8.7mm
23250-1	5" (123mm)	5/16"-24		✓	12000	Medium	5	100g	8.7mm
23250-2	5" (123mm)	5/16"-24	✓		12000	Medium	5	100g	8.7mm
23060-1	6" (148mm)	5/16"-24		✓	12000	Medium	no hole	125g	8.7mm
23060-2	6" (148mm)	5/16"-24	✓		12000	Medium	no hole	125g	8.7mm
23160-1	6" (148mm)	5/16"-24		✓	12000	Medium	6	125g	8.7mm
23160-2	6" (148mm)	5/16"-24	✓		12000	Medium	6	125g	8.7mm

Remark: Use J-hook velcro.

Bevel Edge DA Backing Pads



Item No.	Size	Thread	Velcro	PSA	Max.RPM	Density	Hole	Weight	Thickness
23550-1	5" (123mm)	5/16"-24		✓	12000	Medium	no hole	100g	8.7mm
23550-2	5" (123mm)	5/16"-24	✓		12000	Medium	no hole	100g	8.7mm
23555-1	5" (123mm)	5/16"-24		✓	12000	Medium	5	100g	8.7mm
23555-2	5" (123mm)	5/16"-24	✓		12000	Medium	5	100g	8.7mm
23560-1	6" (148mm)	5/16"-24		✓	12000	Medium	no hole	125g	8.7mm
23560-2	6" (148mm)	5/16"-24	✓		12000	Medium	no hole	125g	8.7mm
23566-1	6" (148mm)	5/16"-24		✓	12000	Medium	6	125g	8.7mm
23566-2	6" (148mm)	5/16"-24	✓		12000	Medium	6	125g	8.7mm

Remark: Use micro hook velcro.



The Pro-Quality level DA pads are designed and manufactured specially for professional air sander building, the pads are 100% tested and they are assured to be in compliance with high requirement of strength, run-out, balance, weight, flatness, and also less vibration.